

# Self-Contained Extractor EX-SC-1530



**Clean smaller areas quickly with this self-contained carpet extractor.**

#### **Easy to use**

The lift-off recovery tank on this compact self-contained carpet extractor lets the operator empty the tank into a drain or sink with ease.

#### **Enhanced user comfort and ease**

Folding handle design adjusts to multiple positions for operator comfort. Plus, convenient trigger grips enable the user to dispense solution evenly through two spray jets. One-button cleaning simplifies operation.

#### **Complete clean**

Clear sight tube allows operators to view solution level and also easily drain excess solution when finished.



## Key Benefits

- Easy-to-use design with lift-off recovery bucket and self-adjusting brush makes this extractor perfect in residential, rentals and small spaces
- Move easily in and out of vehicles or up and down stairs due to its lightweight design, folding handle and recessed transport grips
- Body design and construction delivers years of cleaning performance



# Self-Contained Extractor EX-SC-1530



Features	Specifications*	
<b>Product Name</b>	EX-SC-1530	220 V
<b>Vacuum System</b> Vacuum motor HP Vacuum motor stages Water lift at sealed orifice Airflow through 2 in / 50 mm orifice Vacuum shoe size	1.5 hp / 1.12 kW 2 stage 91.5 in / 2320 mm 103 cfm / 2.9 m <sup>3</sup> 13 in / 330 mm	1.4 hp / 1.04 kW  99 in / 2514 mm 105 cfm / 2.97 m <sup>3</sup>
<b>Recovery System</b> Recovery tank capacity Recovery tank description	4 gal / 15 L Lift-off bucket style	
<b>Brush Drive System</b> Brush motor amp Brush RPM Brush motor RPM Brush width Brush bristle type Brush diameter	.75 A 1200 1800 10.5 in / 266.6 mm Nylon construction, four rows of bristles arranged with 360 degrees spiral 3.375 in / 88 mm	
<b>Solution System</b> Solution pump amps Solution pump pressure Solution pump voltage Solution capacity Solution pump pressure Solution flow Solenoid valve Spray jets	1.25 A 65 psi / 4.1 Bar 120 V 4 gal / 15 L 60 psi / 4.5 Bar 0.7 gpm / 2.6 L / min Electric 2 quick disconnect	220 V
<b>Total Power Consumption</b>	10.6 A / 1272 watts	5.4 A / 1207 watts
<b>Power Cord</b> Power cord length Power cord type	25 ft / 7.62 m 16 gauge	50 ft / 15 m
<b>Optional Accessories</b>	Various wands, hand tools, solution and recovery hoses, etc.	
<b>Dimensions/Weight/Sound Level</b> Length/Width/Height/Weight/Sound	L: 21 in / 533 mm, W: 13 in / 330 mm, H: 29.5 in / 749 mm, Wt: 60 lb / 27 kg, 72 dBA	
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.	

\*Specifications subject to change without notice Note: All 120V models will come with a dual Tennant/Nobles decal