

Single Motor Upright Vacuum



The smart alternative to high priced, unreliable commercial vacuums.

Reduce maintenance costs and downtime

The V-SMU-36 has two quick access clean out ports, and integrated cord holder, thus increasing productivity and lowering service costs verses current commercial vacuums.

Healthy, proven performance

Standard with HEPA 3-stage filtration, the vacuum's cleaning performance is also certified Silver by the Carpet and Rug Institute's (CRI) Seal of Approval program.

Durable and Affordable

Major components have been proven in commercial applications for over 10 years. This vacuum delivers value for money with operating costs up to 58% less than other commercial vacuums.

Be smart. Try this new alternative to the high-priced, unreliable commercial vacuums. It will change your vacuum reality.



Key Benefits

- LEED qualifying with CRI SOA Silver Performance and noise levels less than 70 dBA
- Increase productivity and cleaning coverage with on-board crevice and upholstery tools and up to 30% longer wand reach than competition.
- Easy operator serviceability with no-tool brush and belt replacement

Tennant Australia
Unit 2, Block Y, 391 Park Road (PO Box 116)
Regents Park NSW 2143
Toll Free: 1800 226 843
Ph: +61 2 8718 9718
Fax: +61 2 8718 9719
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand
Unit 5, 103 Cryers Road
East Tamaki Auckland 2013
Ph: +64 9 253 9013
Fax: +64 9 253 9015
www.tennantco.com.nz
contactus@tennantco.com



Single Motor Upright Vacuum



Features	Specifications*
Product Name	V-SMU-36
Vacuum System Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	120 cfm / 204 m ³ /h 1.6 hp / 1.19 kW each Single stage, thermal protected, clean air 1200 watts / 10 A 89 in / 2260 mm
Brush Drive System Brush belt description Brush type Brush size Brush motor HP Brush height	Round drive belt 12 in / 305 mm metal brush roll with natural bristles 2.25 / 57 mm in diameter, 12 in / 305 mm length 0.25 hp / .19 kW Automatic, self-adjusting
Filtration Triple filtration system Triple filtration description Vacuum bag capacity	Filter bag, vac motor filter, and HEPA filter High efficiency (99.97%) at 0.3 micron Fill design, 5.8 qt /6.4 L
Electrical Electrical system Power cord length	Printed circuit board protected 50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
Chassis/Body Construction Construction	Injection molded ABS
Accessories Standard	On-board crevice tool, dusting brush with telescopic aluminum wand with 15' reach (4:1 stretch)
Dimensions / Weight / Sound Level Length Width Height Weight Sound level (at operator's ear)	12.5 in / 320 mm 14.75 in / 370 mm 44 in / 1120 mm 16 lb / 7.3 kg 69.9 dBA
Approvals	C-Tick
Warranty	See your sales representative or authorised distributor for complete warranty details.

*Specifications subject to change without notice

V-SMU-36 AU/NZ 08/11

©2011 Tennant is a registered trademarks of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.

Tennant Australia
Unit 2, Block Y, 391 Park Road (PO Box 116)
Regents Park NSW 2143
Toll Free: 1800 226 843
Ph: +61 2 8718 9718
Fax: +61 2 8718 9719
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand
Unit 5, 103 Cryers Road
East Tamaki Auckland 2013
Ph: +64 9 253 9013
Fax: +64 9 253 9015
www.tennantco.com.nz
contactus@tennantco.com